

RoHS

REV.	EC#	DESCRIPTION	DATE	DRAWING	CHECKED	APPROVED
A0		NEW RELEASE	10/06'20	TEDDY	/	SUNNLY



NOTES:
1. MATERIAL:
   Housing:High Temperature Thermoplastic UL94V-0; Color Black.
   Contacts: Phosphor Bronze.
   Tin 80u" at Solder Tail,
   Selected Gold Flash on Contact Area plating.
   Shell: Stainless.
   Gold Flash on Contact solder Area Over Nickel Plating.
2.Electrical Characteristics:
   Operating voltage :100v AC(rms)/DC.
   Current rating :0.5 A.
   Operating Temperature:-25℃~+85℃.
   Insulation resistance:1000M ohms min. at 500VDC
   Dielectric withstanding voltage :500 VAC/1minute.
   Contact resistance:100m ohms max.
3.Mechanical characteristics
   Insertion force: 2.0kg Max.
   Extraction force: 0.5kg Min.
   Mating durability: 10000 cycles at the speed rate of 400-600 cycles/h; Without distortion of plastic and serious wear and tear in terminal, No signal break.



Pin No.		MICRO SD
PIN1	DAT2	1P
PIN2	CD/DAT3	2P
PIN3	CMD	3P
PIN4	VDD	4P
PIN5	CLK	5P
PIN6	VSS	6P
PIN7	DAT0	7P
PIN8	DAT1	8P
PIN9	CARD DETECT	

开关插卡状态

CIRCUIT:	
CD GROUND	CD GROUND
WITHOUT CARD	CARD INSERTED

MILLIMETERS	INCH
X.° ± 2°	X.° ± 2°
.X ±0.30	.XX ±0.012
.XX ±0.20	.XXX ±0.008
.XXX± 0.10	.XXXX± 0.004


UNITS	MM
MAT'L	SEE NOTES
FINISH	SEE NOTES
QTY	SEE NOTES

KKG


PART NUMBER:	TITLE: (TF014-010) 1.85H P_P TF Card推开一体式 无柱
APPD:	DWG NO.:
CHKD:	
DR:	


SCALE	SHEET	REV.
1:1	1/2	A0

RoHS




客户拉出方向






NOTES


1. 每卷包装数量:1000PCS/每卷
2. 卷带包装方式:




3.每箱包装数量:10000PCS/箱



产品标签
贴在Q'TY：和
PCS字的中间





MILLIMETERS	INCH
X. ± 2'	X. ± 2'
.X ±0.30	.XX ±0.012
.XX ±0.20	.XXX ±0.008
.XXX± 0.10	.XXXX± 0.004

UNITS	MM
MAT'L	SEE NOTES
FINISH	SEE NOTES
QTY	SEE NOTES

KKG

PART NUMBER:	TITLE: (TF014-010) 1.85H P_P TF Card常开一体式 无柱
APPD:	DWG NO.:
CHKD:	
DR:	

SCALE	SHEET	REV.
1:1	2/2	A0