
KKG Electric Co., Ltd.

REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



PIN ASSIGNMENT

P1		P2
PIN1	BLUE	PIN1
PIN2	GREEN	PIN2
PIN3	BLUE	PIN3
PIN4	BLUE	PIN4
PIN5	GREEN	PIN5
PIN6	BLUE	PIN6

Mechanical Performance
1.Terminal/Housing Retention Force: 20N(MIN)
2. Crimping pull out force: 8.9N(MIN)
Electrical
1.Withstanding Voltage: DC 300V
2.Conduction impedance: 3Ω (MAX)
3.Insulation Resistance: 10MΩ (MIN)

Packing specification
20pcs/Bundle, 80pcs/Bag
"*" as the key size contro

* Note: All Materials Meet The "RoHs" !

NO.	Specification
4	UL1015 22AWG(17/0.16TS) OD=2.40mm Green : 1015-22-N1-UL
3	UL1015 22AWG(17/0.16TS) OD=2.40mm Blue : 1015-22-U1-UL
2	Wire to board terminal 4.2mm Female(Tin-Plated) : T42001-F2H-1
1	Wire to board housing 4.2mm 6Circuits HG42001-D06M2TB

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 20/SEP/18	PART NO. CAE-384	ITEM NO. CAE-384	KKG
DESIGN UNITS Metric	X. ±0.30	X.° ±5°	CHECKED BY CHERRY	DATE 20/SEP/18	TITLE Multi-Conductor Cable	REV 0	SHEET NO. 1/1
	X.X ±0.20	X.X° ±2°					
SCALE NA	SIZE A4	X.XX ±0.15	X.XX° ±1°	DRAWN BY CHAOWEI	DATE 20/SEP/18	KKG Electric Co., Ltd.	
		X.XXX ±0.10	X.XXX° ±0.5°				