REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



Electrical
1. Withstanding Voltage: DC 300V
2. Conduction impedance: 3Ω (MAX)
3. Insulation Resistance: 10MΩ (MIN)

Packing specification
50pcs/Bundle, 250pcs/Bag

"*" as the key size control

PIN ASSIGNMENT

P1		P2
PIN1	RED	PIN1
PIN2	ORANGE	PIN2
PIN3	YELLOW	PIN3
PIN4	GREEN	PIN4

* Note: All Materials Meet The "RoHs" !

NO.	Specification
3	UL1007 26AWG(7/0.16TS) 4C Flat Cable Red/Orange/Yellow/Green
2	Wire to board terminal 2.5mm Female(Tin-Plated) T25001-F2H
1	Wire to board housing 2.5mm 4Circuits HG25001-S04M2W1B

THIRD ANGLE PROJECTION		GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 12/AUG/19	PART NO. CAE-070	ITEM NO. CAE-070
DESIGN UNITS Metric		X. ±0.30	X.° ±5°	CHECKED BY CHERRY	DATE 12/AUG/19	TITLE Flat Cable Assemblies	REV 0 / SHEET NO. 1/1
SCALE 5:1	SIZE A4	X.X ±0.20	X.X° ±2°	DRAWN BY ZOEY	DATE 12/AUG/19	KKG Electric Co., Ltd.	
		X.XX ±0.15	X.XX° ±1°				
		X.XXX ±0.10	X.XXX° ±0.5°				