
ROHS

REV.	ECN. #	DESCRIPTION	DATE
A0	————	NEW RELEASE	12/16/20



RECOMMENDED PCB LAYOUT


TOLERANCE: ±0.05

SMT SOLDER AREA

COPPER RESTRICTED AREA
1. TOUCH AREA OF CONTACT TIPS NO ELECTRICAL FUNCTION
2. NO FIRST PCB_LAYOUT CIRCUITS IN THE AREA

NOTES:
1. MATERIAL:
   HOUSING: High Temperature Thermoplastic
   Terminal:Copper Alloy
   Shell: Stainless Steel
2. PLATING:
   Terminal:50u″ Ni UNDERPLATED OVERALL
   G/F PLATED ON CONTACT AREA AND SOLDER AREA
   Sheel:50u″ Ni UNDERPLATED OVERALL
   G/F PLATED ON CONTACT AREA AND SOLDER AREA
3. TECHNICAL SPECIALITY:
   RATED VOLTAGE: 30V AC MAX.
   CURRENT RATING: 0.5A MAX.
   INSULATION RESISTANCE:1000MΩ MIN
   CONTACT REISTANCE:50MΩ MAX
   WITHSTANDING VOLTAGE: 500V AC FOR 1 MINUTES
   OPERATING TEMPERATURE: -40℃~+85℃ Humidity 80% R.H MAX

CRICUIT DIAGRAM FOR CARD DETECT SWITCH




PIIN/NO	ASSIGNMENT
P1	VCC
P2	RST
P3	CLK
P4	Reserved
P5	GND
P6	VPP
P7	I/O
P8	Reserved
P9	Detect Switch
P10	GND

MILLIMETERS	INCH
X.° ±2°	X.° ±2°
.X ±0.30	.X ±0.012
.XX ±0.20	.XX ±0.008
.XXX±0.10	.XXX±0.004

GKKG

TITLE	2.0H 8PIN P-P SIM卡座				DR		
PART NUM.					CHKD		
PROJ.	PAGE	1/2	UNITS	mm	APPD		
	SIZE	A4	SCALE	3:1	DIS NO.		


ROHS




NOTES:

1、Packing quantity per plate: 600PCS/Plate

2、Loading and packing method



3、Total packaging: 3600PCS/Box



Part Number	Description	Quantity
303020154	Carrier band (Lucent , PET W=44 PH=28,T=0.3)	104.16m
303040009	Box (K=K,T=7.0,350*350*340)	1PCS
303060001	PE Bag (T=0.08mm , 730*760*730)	1PCS
303070023	Self-adhesive (W=37.50)	105.96m
303110001	Beam (K=K , T=7.0,95*95*290)	4PCS
303130001	Pearl Wool (340*340*18)	2PCS
303180015	REEL (BLUE , 13Inches*44mm , φ330)	6PCS
102014602	2.0H 8PIN P-P SIM卡座	3600PCS

MILLIMETERS	INCH
X.° ±2°	X.° ±2°
.X ±0.20	.X ±0.012
.XX ±0.10	.XX ±0.008
.XXX±0.05	.XXX±0.004

KKG

TITLE	2.0H 8PIN P-P SIM卡座				DR		
PART NUM.					CHKD		
PROJ.	PAGE	2/2	UNITS	mm	APPD		
	SIZE	A4	SCALE	1:1	DIS NO.		