
KY-2002 Series

2.00mm Pitch Wire to board connectors




SPECIFICATIONS

- Voltage rating: 250V AC/DC
- Current rating: 3A AC/DC
- Withstanding Voltage:800V AC/minute
- Insulation resistance:1000MΩ Min.
- Temperature range:–25 ℃ – +85 ℃
- Contact resistance:20mΩ Max.

KY-2002HD-XX 2.00mm Pitch Dual Row Housing

HOUSING

- Part No.:KY–2002HD–XX
- Poles:2*2–2*18,2*20
- Material:Nylon66 UL 94V–0
- Q'ty:1,000 Pcs/Bag




Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
4	KY–2002HD–04	2.00	6.00
6	KY–2002HD–06	4.00	8.00
8	KY–2002HD–08	6.00	10.00
10	KY–2002HD–10	8.00	12.00
12	KY–2002HD–12	10.00	14.00
14	KY–2002HD–14	12.00	16.00
16	KY–2002HD–16	14.00	18.00
18	KY–2002HD–18	16.00	20.00
20	KY–2002HD–20	18.00	22.00
22	KY–2002HD–22	20.00	24.00
24	KY–2002HD–24	22.00	26.00
26	KY–2002HD–26	24.00	28.00
28	KY–2002HD–28	26.00	30.00
30	KY–2002HD–30	28.00	32.00
32	KY–2002HD–32	30.00	34.00
34	KY–2002HD–34	32.00	36.00
36	KY–2002HD–36	34.00	38.00
40	KY–2002HD–40	38.00	42.00

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw

KY-2002HL-XX 2.00mm Pitch Dual Row Housing




HOUSING

- Part No.:KY–2002HL–XX
- Poles:2*2–2*18
- Material:Nylon66 UL 94V–0
- Q'ty:1,000 Pcs/Bag

Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)		
		A	B	C
6	KY–2002HL–06	4.00	6.50	11.60
8	KY–2002HL–08	6.00	8.50	13.60
10	KY–2002HL–10	8.00	10.50	15.60
12	KY–2002HL–12	10.00	12.50	17.60
14	KY–2002HL–14	12.00	14.50	19.60
16	KY–2002HL–16	14.00	16.50	21.60
18	KY–2002HL–18	16.00	18.50	23.60
20	KY–2002HL–20	18.00	20.50	25.60
22	KY–2002HL–22	20.00	22.50	27.60
24	KY–2002HL–24	22.00	24.50	29.60
26	KY–2002HL–26	24.00	26.50	31.60
28	KY–2002HL–28	26.00	28.50	33.60
30	KY–2002HL–30	28.00	30.50	35.60
32	KY–2002HL–32	30.00	32.50	37.60
34	KY–2002HL–34	32.00	34.50	39.60
36	KY–2002HL–36	34.00	36.50	41.60

KY-2002HSL-XX 2.00mm Pitch Single Row Housing



HOUSING


- Part No.:KY–2002HSL–XX
- Poles:2*2–2*18,2*20
- Material:Nylon66 UL 94V–0
- Q'ty:1,000 Pcs/Bag

Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
2	KY–2002HSL–02	2.00	6.00
3	KY–2002HSL–03	4.00	8.00
4	KY–2002HSL–04	6.00	10.00
5	KY–2002HSL–05	8.00	12.00
6	KY–2002HSL–06	10.00	14.00
7	KY–2002HSL–07	12.00	16.00
8	KY–2002HSL–08	14.00	18.00
9	KY–2002HSL–09	16.00	20.00
10	KY–2002HSL–10	18.00	22.00
11	KY–2002HSL–11	20.00	24.00
12	KY–2002HSL–12	22.00	26.00
13	KY–2002HSL–13	24.00	28.00
14	KY–2002HSL–14	26.00	30.00
15	KY–2002HSL–15	28.00	32.00
16	KY–2002HSL–16	30.00	34.00

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw


KY-2002TPS-10 2.00mm Pitch Terminal



TERMINAL

- Part No.:KY–2002TPS–10
- Thickness:0.20mm
- Material:Phosphor.Bronze
- Finish:Tin Plated
- Q'ty:10,000 Pcs/Reel

KY-2002WS-XX 2.00mm Pitch 180° Dual Row Wafer



WAFER


- Part No.:KY–2002WS–XX
- Poles:2*2–2*18,2*20
- Material:Base:Nylon66 UL 94V–0
- Contact:Brass,Tin Plated
- Q'ty:1,000 Pcs/Bag

Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
4	KY–2002WS–04	2.00	6.00
6	KY–2002WS–06	4.00	8.00
8	KY–2002WS–08	6.00	10.00
10	KY–2002WS–10	8.00	12.00
12	KY–2002WS–12	10.00	14.00
14	KY–2002WS–14	12.00	16.00
16	KY–2002WS–16	14.00	18.00
18	KY–2002WS–18	16.00	20.00
20	KY–2002WS–20	18.00	22.00
22	KY–2002WS–22	20.00	24.00
24	KY–2002WS–24	22.00	26.00
26	KY–2002WS–26	24.00	28.00
28	KY–2002WS–28	26.00	30.00
30	KY–2002WS–30	28.00	32.00
32	KY–2002WS–32	30.00	34.00
34	KY–2002WS–34	32.00	36.00
36	KY–2002WS–36	34.00	38.00
40	KY–2002WS–40	38.00	42.00

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw

KY-2002WR-XX 2.00mm Pitch 90° Dual Row Wafer




WAFER

- Part No.:KY–2002WR–XX
- Poles:2*2–2*18,2*20
- Material:Base:Nylon66 UL 94V–0
- Contact:Brass,Tin Plated
- Q'ty:1,000 Pcs/Bag

Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
4	KY–2002WR–04	2.00	6.00
6	KY–2002WR–06	4.00	8.00
8	KY–2002WR–08	6.00	10.00
10	KY–2002WR–10	8.00	12.00
12	KY–2002WR–12	10.00	14.00
14	KY–2002WR–14	12.00	16.00
16	KY–2002WR–16	14.00	18.00
18	KY–2002WR–18	16.00	20.00
20	KY–2002WR–20	18.00	22.00
22	KY–2002WR–22	20.00	24.00
24	KY–2002WR–24	22.00	26.00
26	KY–2002WR–26	24.00	28.00
28	KY–2002WR–28	26.00	30.00
30	KY–2002WR–30	28.00	32.00
32	KY–2002WR–32	30.00	34.00
34	KY–2002WR–34	32.00	36.00
36	KY–2002WR–36	34.00	38.00
40	KY–2002WR–40	38.00	42.00

KY-2002WSL-XX 2.00mm Pitch 180° Dual Row Wafer



WAFER

- Part No.:KY–2002WSL–XX
- Poles:2*2–2*18,2*20
- Material:Base:Nylon66 UL 94V–0
- Contact:Brass,Tin Plated
- Q'ty:1,000 Pcs/Bag

Ordering Information & Dimensions


POLES	PART NO.	DIMENSION(mm)	
		A	B
4	KY–2002WSL–04	2.00	8.00
6	KY–2002WSL–06	4.00	10.00
8	KY–2002WSL–08	6.00	12.00
10	KY–2002WSL–10	8.00	14.00
12	KY–2002WSL–12	10.00	16.00
14	KY–2002WSL–14	12.00	18.00
16	KY–2002WSL–16	14.00	20.00
18	KY–2002WSL–18	16.00	22.00
20	KY–2002WSL–20	18.00	24.00
22	KY–2002WSL–22	20.00	26.00
24	KY–2002WSL–24	22.00	28.00
26	KY–2002WSL–26	24.00	30.00
28	KY–2002WSL–28	26.00	32.00
30	KY–2002WSL–30	28.00	34.00
32	KY–2002WSL–32	30.00	36.00
34	KY–2002WSL–34	32.00	38.00
36	KY–2002WSL–36	34.00	40.00
40	KY–2002WSL–40	38.00	44.00


TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw

KY-2002WRL-XX 2.00mm Pitch 90° Dual Row Wafer

WAFER

- Part No.:KY–2002WRL–XX
- Poles:2*2–2*18,2*20
- Material:Base:Nylon66 UL 94V–0
- Contact:Brass,Tin Plated
- Q'ty:1,000 Pcs/Bag







P.C.B LAYOUT

Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
4	KY–2002WRL–04	2.00	8.00
6	KY–2002WRL–06	4.00	10.00
8	KY–2002WRL–08	6.00	12.00
10	KY–2002WRL–10	8.00	14.00
12	KY–2002WRL–12	10.00	16.00
14	KY–2002WRL–14	12.00	18.00
16	KY–2002WRL–16	14.00	20.00
18	KY–2002WRL–18	16.00	22.00
20	KY–2002WRL–20	18.00	24.00
22	KY–2002WRL–22	20.00	26.00
24	KY–2002WRL–24	22.00	28.00
26	KY–2002WRL–26	24.00	30.00
28	KY–2002WRL–28	26.00	32.00
30	KY–2002WRL–30	28.00	34.00
32	KY–2002WRL–32	30.00	36.00
34	KY–2002WRL–34	32.00	38.00
36	KY–2002WRL–36	34.00	40.00
40	KY–2002WRL–40	38.00	44.00

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw