


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE  
PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE  
WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
E	ECN 4944: ADDED FRONT & BACK SHELL FINISH, ADDED PKG NOTE, DEL CURRENT RATING	8/3/10	D. CASTRO
F	ECN 7987: UPDATED NOTES TO MATCH SUPPLIER SPEC	6/16/15	D. CASTRO
G	ECN 8860: ADD 'REACH' COMPLIANCY NOTE	7/19/2017	R. CLARK
-	-	-	-

#### NOTES:

#### MATERIAL:

CONNECTOR SHELL: STEEL  
CONNECTOR INSULATOR: THERMOPLASTIC, UL94V-0 RATED  
CONTACTS: BRASS

#### FINISH:

FRONT SHELL: NICKEL PLATED  
BACK SHELL: TIN PLATED  
CONTACTS: 5  $\mu$ m SELECTIVE GOLD  
SOLDER CUPS: TIN PLATED

#### ELECTRICAL:

DIELECTRIC WITHSTANDING VOLTAGE: 1000 VAC rms  
INSULATION RESISTANCE: 500M $\Omega$  @ DC 500V  
CONTACT RESISTANCE: 25 MILLIOHMS MAX  
CURRENT RATING: 1 AMP

#### MISCELLANEOUS:

OPERATING TEMPERATURE: -55°C TO +105°C  
CONNECTOR SHALL BE PACKAGED IN ACCORDANCE WITH  
L-COM SPEC PS-0031.

#### REGULATORY COMPLIANCE:

CE2011/65/EU (RoHS DIRECTIVE)  
REACH REGULATION (EC) No 1907/2006

CATALOG #	PACKAGING
9PS	1/BAG
9PS-TRAY	50/TRAY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] OVERALL CABLE LENGTH TOLERANCE: ≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2 [51] / -0 >60 [1524] ≤120 [3048] = +4 [102] / -0 >120 [3048] ≤300 [7620] = +6 [152] / -0 >300 [7620] = +3% / -0% ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 .XX = ±.02 .XXX = ±.005 PROJECTION 	APPROVALS	DATE		
	DRAWN BY B. MAZEJKA	11/10/2003		
	CHECKED BY C. MCCORMICK	12/08/2003	CATEGORY D-SUBMINIATURE	
	APPROVED BY D. PARHAM	12/08/2003	PRODUCT DESCRIPTION FEMALE DB9F SOLDER CUP CONNECTOR	
COLOR VARIATIONS MAY OCCUR		SIZE <b>A</b>	FSCM NO. <b>43321</b>	DWG. NO. D-SUB-9PS
1AC08-017		SCALE: NONE	CAD FILE: SD9S.SLDDRW	REV. <b>G</b>
		SHEET 1 OF 1		