



REV.	ECN.NO.	APPD.
A0	/	/

规格说明: specifications;
电气性能: electrical:
1. 额定电流: current rating
1. 5A/contact terminal
2. 额定电压: voltage rating
30V DC
3. 接触阻抗: contact resistance
30milliohms MAX
4. 耐电压: dielectric withstanding voitage:
500V AC atsea level
5. 绝缘阻抗: Insulation resistance:
1000MEGA ohms MIN
物理性能: mechanical:
1. 插拔力: cnnector mate and dnmate force
mate force:3.75kgf MAX
unmate force:1.02kgf MIN
2. 端子保持力: terminal retenion
1. 2kgf MIN
原材料: material:
1. 塑胶: housing:
hing temperature tternaplastics,
UL 94V-0 PBT white
2. 端子:contact :plated cold in mating area:
tin on solder talls
2. 外壳: shell:
nickel panting

U241-0721-XXX0X7
G:半金G/F
1:半金1u"
3:半金3u"
5:半金5u"
8:半金15u"
9:镀全金1u"
1:吸塑盒
3:载带冷封
8:载带热封
1:黑色
2:白色
3:米黄色
E:蓝色300C-3
7:蓝色300C

TOLERANCE UNLESS OTHERWISE SPECIFIED									
.XXX ±0.10	.XX ±0.20	.X ±0.30						.X* ±3"	.XX* ±2"
APPROVED		PART NAME:	USB BF 90度						
CHECKED		PART No:	USB-U247			C			
DRAWED		PROJECTION:	UNIT:	SCALE	SHEET	REV.			
DATE			mm	1:1	10F1	A0			