
REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD



PIN ASSIGNMENT

P1

PIN1	BLACK	Tinned
PIN2	RED	Tinned

Electrical
1. Withstanding Voltage: DC 300V
2. Conduction impedance: 1Ω (MAX)
3. Insulation Resistance: 10MΩ (MIN)

Packing specification
1. 50pcs/Bundle, 200pcs/Bag

* Note: All Materials Meet The "RoHs" !

NO.	Specification
3	Wire to board terminal 1.5mm Female(Tin-Plated) T15003-F2H
2	Wire to board housing 1.5mm 2Circuits HG15003-S02M2W1B
1	UL1571 28AWG 1C OD 0.6 RED/BLACK

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY FRANK	DATE 28/FEB/19	PART NO. CAE-620 / ITEM NO. CAE-620
	X. ±0.30	X.° ±5°	CHECKED BY CHERRY	DATE 28/FEB/19	TITLE: Single Conductor Cable
DESIGN UNITS Metric	X.X ±0.20	X.X° ±2°			REV 1 / SHEET NO. 1/1
SCALE 5:1 / SIZE A4	X.XX ±0.15	X.XX° ±1°	DRAWN BY CHAOWEI	DATE 28/FEB/19	KKG Electric Co., Ltd.
	X.XXX ±0.10	X.XXX° ±0.5°			