REV	LOCATIONS	DESCRIPTION	DATE	REVISER	APPD

SPECIFICATIONS

Electrical
Current Rating: 0.5A AC(rms)/DC
Voltage Rating: 60V AC(rms)/DC
Withstanding Voltage: 200V AC r.m.s
Temperature Range-Operating: -40℃~+85℃

Recommended storage condition
Temperature: 15℃~25℃
Humidity: 30~60%(RH)







Drawing	Item	Dimension
N	Number of conductors	24
P	Pitch	0.50±0.05
SP	Total Pitch	11.5±0.07
W	Total Width	12.5±0.07
TL	Total Length	80±3.0
M	Margin Width	0.5±0.07
T	Terminal Thickness	0.30±0.05
Ct	Conductor Thickness	0.035
Cw	Conductor Width	0.30±0.025
S1	Strip length	3.0±0.5
S2	Strip length	3.0±0.5
S3	Supporting Tape Length	6.0±1.0
S4	Supporting Tape Length	6.0±1.0
Tt	Thickness insulation	0.12±0.03
Supporting Tape Thickness		0.225mm
PET(Insulation)		0.043mm (20624)
PET(Insulation)		0.043mm White

THIRD ANGLE PROJECTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		APPROVE BY VERNON	DATE 25/NOV/15	PART NO. FPC-024	ITEM NO. FPC-024	KKG
DESIGN UNITS Metric	X. ±0.30	X.° ±5°	CHECKED BY CHERRY	DATE 25/NOV/15	TITLE FLEXIBLE FLAT CABLE	REV 0	SHEET NO. 1/1
SCALE 5:1 / SIZE A4	X.X ±0.20	X.X° ±2°					
	X.XX ±0.15	X.XX° ±1°	DRAWN BY KATE	DATE 25/NOV/15	KKG Electric Co., Ltd.		
	X.XXX ±0.10	X.XXX° ±0.5°					