
1.25mm Pitch Wire to board connectors

KY-1253 Series




SPECIFICATIONS

- Voltage rating: 150V AC/DC
- Current rating: 1A AC/DC
- Withstanding Voltage:500V AC/minute
- Insulation resistance:500MΩ Min.
- Temperature range:–25 ℃ – +85 ℃
- Contact resistance:20mΩ Max.

KY-1253HS-XX 1.25mm Pitch Housing

HOUSING

- Part No.:KY–1253HS–XX
- Poles:2–15,20,25,30
- Material:Nylon 66 UL 94V–0(Beige)
- Q'ty:1,000Pcs/Bag




Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
2	KY–1253HS–02	1.25	4.45
3	KY–1253HS–03	2.50	5.70
4	KY–1253HS–04	3.75	6.95
5	KY–1253HS–05	5.00	8.20
6	KY–1253HS–06	6.25	9.45
7	KY–1253HS–07	7.50	10.70
8	KY–1253HS–08	8.75	11.95
9	KY–1253HS–09	10.00	13.20
10	KY–1253HS–10	11.25	14.45
11	KY–1253HS–11	12.50	15.70
12	KY–1253HS–12	13.75	16.95
13	KY–1253HS–13	15.00	18.20
14	KY–1253HS–14	16.25	19.45
15	KY–1253HS–15	17.50	20.70
20	KY–1253HS–20	23.75	26.95
25	KY–1253HS–25	30.00	33.20
30	KY–1253HS–30	36.25	39.45

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw


KY-1253TPS-10 1.25mm Pitch Terminal



TERMINAL

- Part No.:KY–1253TPS–10
- Thickness:0.15mm
- Material:Phosphor Bronze
- Finish:Tin Plated
- Q'ty:15,000Pcs/Reel

KY-1253WRS-XX 1.25mm Pitch 90° Wafer SMT Type



WAFER

- Part No.:KY–1253WRS–XX
- Poles:2–15,20,25,30
- Material:Base:Nylon6T UL 94V–0
- Contact:Brass,Tin plated
- Q'ty:1,500Pcs/Bag

Ordering Information & Dimensions


POLES	PART NO.	DIMENSION(mm)		
		A	B	C
2	KY–1253WRS–02	1.25	7.45	6.45
3	KY–1253WRS–03	2.50	8.70	7.50
4	KY–1253WRS–04	3.75	9.95	8.75
5	KY–1253WRS–05	5.00	11.20	10.00
6	KY–1253WRS–06	6.25	12.45	11.25
7	KY–1253WRS–07	7.50	13.70	12.50
8	KY–1253WRS–08	8.75	14.95	13.75
9	KY–1253WRS–09	10.00	16.20	15.00
10	KY–1253WRS–10	11.25	17.45	16.25
11	KY–1253WRS–11	12.50	18.70	17.50
12	KY–1253WRS–12	13.75	19.95	18.75
13	KY–1253WRS–13	15.00	21.20	20.00
14	KY–1253WRS–14	16.25	22.45	21.25
15	KY–1253WRS–15	17.50	23.70	22.50
20	KY–1253WRS–20	23.75	29.95	28.75
25	KY–1253WRS–25	30.00	36.20	35.00
30	KY–1253WRS–30	36.25	42.45	41.25


TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw

KY-1253WRD-XX 1.25mm Pitch 90° Wafer With Polarizing Peg SMT Type

WAFER

- Part No.:KY–1253WRD–XX
- Poles:2–15,20,25,30
- Material:Base:Nylon6T UL 94V–0
- Contact:Brass,Tin plated
- Q'ty:1,500Pcs/Bag





P.C.B LAYOUT

Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)		
		A	B	C
2	KY–1253WRD–02	1.25	7.45	6.45
3	KY–1253WRD–03	2.50	8.70	7.50
4	KY–1253WRD–04	3.75	9.95	8.75
5	KY–1253WRD–05	5.00	11.20	10.00
6	KY–1253WRD–06	6.25	12.45	11.25
7	KY–1253WRD–07	7.50	13.70	12.50
8	KY–1253WRD–08	8.75	14.95	13.75
9	KY–1253WRD–09	10.00	16.20	15.00
10	KY–1253WRD–10	11.25	17.45	16.25
11	KY–1253WRD–11	12.50	18.70	17.50
12	KY–1253WRD–12	13.75	19.95	18.75
13	KY–1253WRD–13	15.00	21.20	20.00
14	KY–1253WRD–14	16.25	22.45	21.25
15	KY–1253WRD–15	17.50	23.70	22.50
20	KY–1253WRD–20	23.75	29.95	28.75
25	KY–1253WRD–25	30.00	36.20	35.00
30	KY–1253WRD–30	36.25	42.45	41.25

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw