



SPECIFICATIONS


- Voltage rating: 30V AC/DC
- Current rating: 1.5A AC/DC
- Withstanding Voltage:500V AC/minute
- Insulation resistance:1000MΩ Min.
- Temperature range:–40 ℃ – +105 ℃
- Contact resistance:20mΩ Max.

KY-1271HC-X05 1.27mm Pitch Sata


SATA


- Part No.:KY–1271HC–X05
- Material:PBT UL 94V–0
- Q'ty:1,000 Pcs/Bag





180 度上盖






90 度上盖

Ordering Information & Dimensions

PART NO.	A	WIRE RANGE
KY–1271HC–A05	0.65	18#
KY–1271HC–B05	0.60	20#
KY–1271HC–C05	0.52	22#

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw


KY-1271HS-05 1.27mm Pitch Sata



SATA

- Part No.:KY–1271HS–05
- Material:PBT UL 94V–0
- Q'ty:1000 Pcs/Bag

KY-1271TPS-30 1.27mm Pitch Terminal



TERMINAL

- Part No.:KY–1271TPS–30
- Thickness:0.25mm
- Material:Phosphor Bronze
- Finish:Gold Plated
- Q'ty:10,000 Pcs/Reel

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw