


THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	02/05/04	M.C.CORMICK
B	ECN# 2731 - ADDED ROHS STAMP	10/23/07	D.GRIFFIN
C	ECN 4278: ADDED OPERATING TEMPERATURE RANGE AND PACKAGING	9/30/09	D.FRISIELLO



RoHS Compliant ✓

NOTES:

1. IP (INGRESS PROTECTION) RATING: 67.
2. OPERATING TEMPERATURE RANGE: -40°C TO +105°C.
3. COMPONENT SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN INCHES [mm] DIMENSIONAL TOLERANCES: .X = ±.1 .XX = ±.03 .XXX = ±.005 ANGULAR TOLERANCES: ALL = ± 1° PROJECTION 	APPROVALS	DATE			
	DRAWN BY C.MCCORMICK	02/05/2004			CATEGORY
	CHECKED BY D.PARHAM	02/05/2004	DATA CABLING		
	APPROVED BY R.CARRICK	02/05/2004	PRODUCT DESCRIPTION DB15 FEMALE WATERPROOF SOLDER		
	CONFIGURATION DETAILS OF UNDIMENSIONED FEATURES MAY VARY	SIZE A	FSCM NO. 43321	DWG. NO. D-SUB-15PA-1	REV. C
	COLOR VARIATIONS MAY OCCUR	SCALE: NONE	CAD FILE: WPSD15S.SLDDRW	SHEET 1 OF 1	