



额定电流: 0.5A
额定电压: 50V
耐电压: 500V
接触电阻: $\leq 20\text{m}\Omega$
绝缘电阻: $800\text{M}\Omega$
工作温度: $-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$

X. ± 0.3	X° ± 5°	mm	UNITS	NAME (INTENDED USE)				
.X ± 0.25	.X° ± 2°		MAT' L	1.0mm FPC (E型) 半包上接 (H=2.5)				
.XX ± 0.20	.XX° ± 1°	FINISH		PART NO. (INTENDED USE)		TITLE:		
.XXX ± 0.10	.XXX° ± 0.5°		Q' TY	1. 0K-ES-nPWB		1. 0mm FPC (E型) 半包上接 (H=2.5)		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DE RUI ELECTRON FACTORY AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DE RUI ELECTRON FACTORY		APPD:		DWG NO.:				
		CHKD:		100K12-EXB0000000				
			DR: YLZ 2011.09.28		SCALE	SHEET	REV	
					1/1	1/1	A	