
REVISION DATA			
ITEM	DESCRIPTION	DATE	REMARK
B			

2.54mm Pitch wire to board connectors


■ SPECIFICATIONS

- Voltage rating: 250V AC/DC
- Current rating: 3A AC/DC
- Withstanding Voltage: 1000V AC/minute
- Insulation resistance: 1000MΩ Min.
- Temperature range: -25° C - +85° C
- Contact resistance: 20mΩ Max.



■ HOUSING

- Part No.: KY-2541HS-XX
- Poles: 1*40
- Material: PBT UL 94V-0
- Q'TY: 1000 Pcs/Bag



POLES	PART NO.	DIMENSION(mm)	
		A	B
1	KY-2541HS-01	\	2.54
2	KY-2541HS-02	2.54	5.08
3	KY-2541HS-03	5.08	7.62
4	KY-2541HS-04	7.62	10.16
5	KY-2541HS-05	10.16	12.70
6	KY-2541HS-06	12.70	15.24
7	KY-2541HS-07	15.24	17.78
8	KY-2541HS-08	17.78	20.32
9	KY-2541HS-09	20.32	22.86
10	KY-2541HS-10	22.86	25.40
...	...	...	...
20	KY-2541HS-20	48.26	50.80
...	...	...	...
30	KY-2541HS-30	73.66	76.20
...	...	...	...
40	KY-2541HS-40	99.06	101.60

KKG

绘图(DRAWN)	杨 玉	投影(PROJECT)		公差(TOLERNCE)	料 号 (PART NO)	KY-2541HS-XX	页 次 (PAGE)
审核(CHECKED)		单位(UNIT)	mm	0.0 ±2°	图 号 (DRAW NO)	LJ1KY-2541HS-XX	1/1
核准(APPROVE)		比例(SCALE)	FIT	0.0 ±0.30	品 名 (NAME)	2.54mm PITCH HOUSING	
		版本(EDITION)	A	0.00 ±0.20			
		日期(DATE)	2009.8.31	0.000 ±0.10			