REVISION DATA			
ITEM	DESCRIPTION	DATE	REMARK
B			


2.54mm Pitch wire to wire/board connectors


■ SPECIFICATIONS

- Voltage rating: 250V AC/DC
- Current rating: 3A AC/DC
- Withstanding Voltage: 1000V AC/minute
- Insulation resistance: 1000MΩ Min.
- Temperature range: -25° C - +85° C
- Contact resistance: 20mΩ Max.


■ HOUSING

- Part No.: KY-2543HL-XX
- Poles: 2-26
- Material: PA66 UL 94V-0
- Q'TY: 1000 Pcs/Bag







3 PIN



2 PIN





POLES	PART NO.	DIMENSION (mm)	
		A	B
2	KY-2543HL-02	2.54	5.08
3	KY-2543HL-03	5.08	7.62
4	KY-2543HL-04	7.62	10.16
5	KY-2543HL-05	10.16	12.70
6	KY-2543HL-06	12.70	15.24
7	KY-2543HL-07	15.24	17.78
8	KY-2543HL-08	17.78	20.32
9	KY-2543HL-09	20.32	22.86
10	KY-2543HL-10	22.86	25.40
11	KY-2543HL-11	25.40	27.94
12	KY-2543HL-12	27.94	30.48
13	KY-2543HL-13	30.48	33.02
14	KY-2543HL-14	33.02	35.56
15	KY-2543HL-15	35.56	38.10
16	KY-2543HL-16	38.10	40.64
17	KY-2543HL-17	40.64	43.18
18	KY-2543HL-18	43.18	45.72
19	KY-2543HL-19	45.72	48.26
20	KY-2543HL-20	48.26	50.80
21	KY-2543HL-21	50.80	53.34
22	KY-2543HL-22	53.34	55.88
23	KY-2543HL-23	55.88	58.42
24	KY-2543HL-24	58.42	60.96
25	KY-2543HL-25	60.96	63.50
26	KY-2543HL-26	63.50	66.04

KKG

绘图 (DRAWN)	杨 玉	投影 (PROJECT)		公差 (TOLERNCE)	料 号 (PART NO)	KY-2543HL-XX	页 次 (PAGE)
审核 (CHECKED)		单位 (UNIT)	mm	0.0 ±2°	图 号 (DRAW NO)	LJ1KY-2543HL-XX	1/1
核准 (APPROVE)		比例 (SCALE)	FIT	0.0 ±0.30	品 名 (NAME)	2.54mm PITCH HOUSING	
		版本 (EDITION)	A	0.00 ±0.20			
		日期 (DATE)	2009.6.29	0.000 ±0.10			