
2.00mm Pitch Wire to board connectors

KY-2011 Series




SPECIFICATIONS


- Voltage rating: 125V AC/DC
- Current rating: 2A AC/DC
- Withstanding Voltage:1000V AC/minute
- Insulation resistance:1000MΩ Min.
- Temperature range:–25 ℃ – +85 ℃
- Contact resistance10mΩ Max.

KY-2011HS-XX 2.00mm Pitch Housing

HOUSING

- Part No.:KY–2011HS–XX
- Poles:2–15
- Material:Nylon66 UL 94V–0
- Q'ty:1,000 Pcs/Bag






Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)		
		A	B	C
2	KY–2011HS–02	6.00	2.00	4.80
3	KY–2011HS–03	8.00	4.00	6.80
4	KY–2011HS–04	10.00	6.00	8.80
5	KY–2011HS–05	12.00	8.00	10.80
6	KY–2011HS–06	14.00	10.00	12.80
7	KY–2011HS–07	16.00	12.00	14.80
8	KY–2011HS–08	18.00	14.00	16.80
9	KY–2011HS–09	20.00	16.00	18.80
10	KY–2011HS–10	22.00	18.00	20.80
11	KY–2011HS–11	24.00	20.00	22.80
12	KY–2011HS–12	26.00	22.00	24.80
13	KY–2011HS–13	28.00	24.00	26.80
14	KY–2011HS–14	30.00	26.00	28.80
15	KY–2011HS–15	32.00	28.00	30.80

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw


KY-2011TPS-10 2.00mm Pitch Terminal



TERMINAL

- Part No.:KY–2011TPS–10
- Thickness:0.25mm
- Material:Phosphor.Bronze
- Applicable Wires:AWG#22–#28
- Finish:Tin Plated
- Q'ty:10,000 Pcs/Reel

KY-2011WS-XX 2.00mm Pitch 180° Wafer



WAFER

- Part No.:KY–2011WS–XX
- Poles:2–15
- Material:Base:Nylon 66 UL 94V–0
- Contact:Brass,Tin Plated
- Q'ty:1,000 Pcs/Bag

Ordering Information & Dimensions


POLES	PART NO.	DIMENSION(mm)	
		A	B
2	KY–2011WS–02	2.00	6.00
3	KY–2011WS–03	4.00	8.00
4	KY–2011WS–04	6.00	10.00
5	KY–2011WS–05	8.00	12.00
6	KY–2011WS–06	10.00	14.00
7	KY–2011WS–07	12.00	16.00
8	KY–2011WS–08	14.00	18.00
9	KY–2011WS–09	16.00	20.00
10	KY–2011WS–10	18.00	22.00
11	KY–2011WS–11	20.00	24.00
12	KY–2011WS–12	22.00	26.00
13	KY–2011WS–13	24.00	28.00
14	KY–2011WS–14	26.00	30.00
15	KY–2011WS–15	28.00	32.00

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw


KY-2011WR-XX 2.00mm Pitch 90° Wafer

WAFER

- Part No.:KY–2011WR–XX
- Poles:2–15
- Material:Base:Nylon 66 UL 94V–0
- Contact:Brass,Tin Plated
- Q'ty:1,000 Pcs/Bag



P.C.B Layout



Ordering Information & Dimensions

POLES	PART NO.	DIMENSION(mm)	
		A	B
2	KY–2011WR–02	2.00	6.00
3	KY–2011WR–03	4.00	8.00
4	KY–2011WR–04	6.00	10.00
5	KY–2011WR–05	8.00	12.00
6	KY–2011WR–06	10.00	14.00
7	KY–2011WR–07	12.00	16.00
8	KY–2011WR–08	14.00	18.00
9	KY–2011WR–09	16.00	20.00
10	KY–2011WR–10	18.00	22.00
11	KY–2011WR–11	20.00	24.00
12	KY–2011WR–12	22.00	26.00
13	KY–2011WR–13	24.00	28.00
14	KY–2011WR–14	26.00	30.00
15	KY–2011WR–15	28.00	32.00

TEL:+86(0)769-82036866 82076766 FAX:+86(0)769-82076788
E-mail£ºkkg@kkg.tw Http://www.kkg.tw