





额定电流: 1A
 额定电压: 200V
 耐电压: 500V
 接触电阻: $\leq 20\text{m}\Omega$
 绝缘电阻: $500\text{M}\Omega$
 工作温度: $-20^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 塑件(材质): PBT, UL94V-0
 插簧(材质): 磷青铜, 镀锡/镀金

孔位	A	B	C
4	3.75	6.25	8.55
5	5.00	7.50	9.80
6	6.25	8.75	11.05
7	7.50	10.00	12.30
8	8.75	11.25	13.55
9	10.00	12.50	14.80
10	11.25	13.75	16.05
11	12.50	15.00	17.30
12	13.75	16.25	18.55
13	15.00	17.50	19.80
14	16.25	18.75	21.05
15	17.50	20.00	22.30
16	18.75	21.25	23.55
17	20.00	22.50	24.80
18	21.25	23.75	26.05
19	22.50	25.00	27.30
20	23.75	26.25	28.55
21	25.00	27.50	29.80
22	26.25	28.75	31.05
23	27.50	30.00	32.30
24	28.75	31.25	33.55
25	30.00	32.50	34.80
26	31.25	33.75	36.05
27	32.50	35.00	37.30
28	33.75	36.25	38.55
29	35.00	37.50	39.80
30	36.25	38.75	41.05
31	37.50	40.00	42.30
32	38.75	41.25	43.55
33	40.00	42.50	44.80
34	41.25	43.75	46.05
35	42.50	45.00	47.30
36	43.75	46.25	48.55
37	45.00	47.50	49.80
38	46.25	48.75	51.05
39	47.50	50.00	52.30
40	48.75	51.25	53.55

X. ± 0.3	X° ± 5°	mm	UNITS	NAME (INTENDED USE)				
.X ± 0.25	.X° ± 2°		MAT' L			1. 25mm FPC (A型) 弯插 (正脚)		
.XX ± 0.20	.XX° ± 1°	FINISH	PART NO. (INTENDED USE)	TITLE:	1. 25mm FPC (A型) 弯插 (正脚)			
.XXX ± 0.10	.XXX° ± 0.5°					1. 25-A-nPw		
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DE RUI ELECTRON FACTORY AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF DE RUI ELECTRON FACTORY		Q' TY	APPD:	DWG NO.:	125N03-AUH0000000			
			CHKD:			SCALE	SHEET	REV.
			DR:			YLZ 2011.09.28	1/1	1/1