

REV.	ECN.NO.	APPD.
A	/	pcy

- NOTES:
- 1. MATERIAL:
 - 1.1 Housing: thermoplastic plastics
 - 1.2 terminals: Copper Alloy
 - Gold plated in contact area:
 - Tin plated in termination
 - Nickel Plated overall
 - 1.3 Shell: Steel&Copper Alloy
 - Nickel/Au Plated overall
 - 2. ELECTRICAL CHARACTERISTICS:
 - 2.1 Rating Current : 0.5 Ampere
 - 2.2 Rating Voltage : 40 V Max
 - 2.3 Contact Resistance: 30 Milli ohms
 - 2.4 Insulation Resistance: 100 Mega ohms Min.
 - 3. MECHANICAL CHARACTERISTICS:
 - 3.1 Connector Mating force: 4.5kg MAX
 - 3.2 Connector Unmating force: 1.0Kg min
 - 3.3 Durability: 10000Cycles.
 - 4. ENVIRONMENT CHARACTERISTICS:
 - 4.1 Operating temperature: -55℃ to +85℃
 - 4.2 Storage temperature: -20℃ to +85℃

HD23-041X-XXX0X1

- 1:Iron alloy
Ni plating

5:Copper alloy
Ni plating

4:Iron alloy
Au plating

8:Copper alloy
Au plating

1:Au 1u", 3:Au 3u"

5:Au 5u", 7:Au 10u"

8:Au 15u", A:Au 30u"
- 1:tray

2:Tube

8:Tape&Reel



9:Tape&Reel+Mylar

1:Black

5:PA9T

2:PBTP

6:LCP

TOLERANCE UNLESS OTHERWISE SPECIFIED						
.XXX	±0.10	.X*	±3*			
.XX	±0.20	.XX*	±2*			
.X	±0.30					
APPROVED		PART NAME:	HDMI 19P/F 三排90度 单耳(孔距8.975)			
CHECKED		PART No:	HD23-041X-XXX0X1		C	
DRAWN	pengchaoyong	PROJECTION:	UNIT:	SCALE	SHEET	REV.
DATE	2014.12.3		mm	1:1	1 OF 1	A