




REV.	ECN.NO.	APPD.
A	/	pcy

















RECOMMENDED P.C.B HOLE LAYOUT
COMPONENT SIDE VIEW(TOLERANCE: +/−0.05)

NOTES:
1.MATERIAL:
1.1 Housing:thermoplastic plastics
1.2 terminals:Copper Alloy
Gold plated in contact area:
Tin plated in termination
Nickel Plated overall
1.3 Shell:Steel&Copper Alloy
Nickel/Au Plated overall
2.ELECTRICAL CHARACTERISTICS:
2.1 Rating Current :0.5 Ampere
2.2 Rating Voltage :40 V Max
2.3 Contact Resistance:30 Milli ohms
2.4 Insulation Resistance:100 Mega ohms Min.
3.MECHANICAL CHARACTERISTICS:
3.1 Connector Mating force：4.5kg MAX
3.2 Connector Unmating force:1.0Kg min
3.3 Durability:10000Cycles.
4.ENVIRONMENT CHARACTERISTICS:
4.1 Operating temperature:−20℃ to +85℃
4.2 Storage temperature:−20℃ to +65℃

TOLERANCE UNLESS OTHERWISE SPECIFIED						
.XXX ±0.10 .XX ±0.20 .X ±0.30		.X° ±3° .XX° ±2°	KKG			
APPROVED		PART NAME:	HDMI 19P/F SMT 无后盖 无凸点			
CHECKED		PART No:				C
DRAWED	pengchaoyong	PROJECTION:	UNIT:	SCALE	SHEET	REV.
DATE	2014.12.4		mm	1:1	1 OF 1	A