



HSF Pb RoHS








RECOMMENDED PCB LAYOUT
TOP VIEW(.XX±0.05)



SPECIFICATIONS:

1. VOLTAGE RATING:30 V

3. WITHSTAND VOLTAGE:500 V
4. INSULATION RESISTANCE:500 MEG OHM MIN
5. CONTACT RESISTANCE:30 MILL.OHM MAX
6. OPERATION TEMPERATURE:-55° C TO +125° C
7. PLASTIC MATERIAL:LCP BLACK
8. CONTACT POINT MATERIAL:BRASS C2680,GOLD PLATING
9. LIFE TEST:10000 TIMES MIN



PIN	PART NO.	DIM A	DIM B
2P	ABT32-029DXD	8.0	6.0
3P	ABT32-039DXD	12.0	10.0
4P	ABT32-049DXD	16.0	14.0
5P	ABT32-059DXD	20.0	18.0
6P	ABT32-069DXD	24.0	22.0

REV	DESCRIPTION	DATE

Unless Otherwise specified tolerance
X. ±0.35 X.XX: ±0.20
X.X: ±0.25 X.XXX: ±0.15

SCALE: As Shown	UNIT: mm
DRAW Wu Feng Rong	DATE 22/07/2020
CHECK BobYang	DATE 22/07/2020

3rd ANGLE PROJECTION

KKG

TITLE: 4.0 PITCH 3PIN BATTERY FEMALE CONNECTOR

DRAWING NO: BC-320

PRODUCT NO: BC-320