



文件类型:	产品图面

REV.	ECN NO.	DESCRIPTION	DRWN	APPD.	DATE.









原材料Material:

1.塑胶Housing: Hing Temperature thermaplastics,UL94v-0 PBT/LCP White/Black

2.端子Contact: Copper Alloy C2680

3.外壳Shell: Copper Alloy C2680/SPCC

规格说明Specification:

1.额定电流Current rating:1.0A/contact terminal

2.额定电压Voltage Rating 30V DC

3.接触阻抗Contact resistance: 30 milliohms MAX

4.耐电压Dielectnic Withstanding Voitage 500 V AC For one minute

5.绝缘阻抗Insulation resistance:1000MEGA ohms MIN.

6.插拔力Cnnector Mate and Unmate ForceMate force:3.57kgf(MAX) Unmate force:1.02kgf(MIN)

7.端子保持力:Terminal Retenion 0.5kgf(MIN)

8.端子电镀Contact Electroplate:Piated Gold in Mating Area; Tin On Solder Talls

9.外壳电镀Shell Electroplate; Nickel Plating

备注Note:

端子电镀: 01;Au1u"; 03;Au3u"; 05;Au5u" 10;Au10u"; 15;Au15u"; 30;Au30u"

主体颜色:白色,黑色,红色,橙色,蓝色,绿色,紫色等 (可根据客户需求定制各种颜色)

UNITS	SCALE
MM	1:1

GENERAL TOLERANCE

X. ±0.30
X.X ±0.20
X.XX ±0.10
X.° ±3°
X.X° ±2°

GKKG

DR. Lila	TITLE: USB AF 10.0 DIP前二脚(反向)无卷边6.3H		
CHK. Loran		DWG NO: USB-UE001Z	
APPD. LIGUIYUAN	DATE: 2011.06.28	P	PART NO: / SIZE A4